

PHYSICAL PROPERTIES

Appearance Black liquid	Flash Point > 105°F	Viscosity < 1,000 cP @ 77°F
Asphalt by Weight 60–65% (ASTM D-41, Type II)	Maximum VOC 350 g/L	Water Vapor Permeance < 0.02
Color Black	Maximum VOS 2.9 lbs./gal.	Weight per Gallon 7.5–7.9 lbs.
Drying Time @ 50% R.H. 68°F (20°C) Touch 3 hrs. Set 24 hrs.	Solids by Weight 60–65%	

APPROVALS AND CERTIFICATIONS

Meets ASTM D-41, Type II

DESCRIPTION

EnduraRoof Asphalt Primer is a thin penetrating solution of selected asphalt base in a petroleum solvent. It readily penetrates the pores of the material to which it is applied and seals surfaces to provide a firm bond for asphalt coatings—hot or cold, cutback types.

USAGE

EnduraRoof Asphalt Primer is an excellent material for use as a general priming coat over smooth surface roofs, concrete, cinder block, brick and metal surfaces. Used to prime surfaces over which built-up roofing, waterproofing or other asphalt coatings are to be applied.

SURFACE PREPARATION

All surfaces to be primed must be dry and swept or brushed clean and free of grease, oil, rust, scale, loose paint and dirt. Allow primer to dry thoroughly before applying coatings or adhesives.

COVERAGE

Coverage is 100–500 sq. ft./gal., depending on porosity of surface. Avoid over-application and build-up of surface film.

CLEAN-UP

Equipment can be cleaned with mineral spirits. Use care in handling solvents. Clean hands with a waterless hand cleaner.

PACKAGING

5 gallon/18.93 liter (39.1 lbs.)

EnduraRoof Asphalt Primer

PRECAUTIONS

Do not heat container or store at temperatures greater than 110°F. When transporting this product, be sure the pail is secured, and the lid is tight. Do not allow pail to tumble as this may loosen the lid and allow leakage to occur. **CLOSE AIR INTAKES ON ROOF UNTIL SOLVENTS DISSIPATE!**

NOTE: This coating, like all asphalt-based products, forms a small amount of water-soluble material as it weathers. Normally this is not noticeable because the rain washes it away. However, roofs having a pitch less than ½" per foot, or ones having poor drainage, will accentuate the problem by allowing water to stand in low spots, thus concentrating the water-soluble material. If there is no rainfall, hose these roofs off to remove the water soluble. Frequent inspection of these roofs is recommended because abnormally rapid deterioration of any roofing material may occur where water stands for long periods.

CAUTION

CAUTION! COMBUSTIBLE! Contains petroleum distillate. Keep away from heat and flame. Do not heat container or store at temperatures greater than 110°F. **CLOSE AIR INTAKES** until solvents dissipate. Contains volatile solvents that might contaminate potable water. Close container after each use. Dispose of container and unused contents in accordance with Local, State and Federal regulations.

DANGER! HARMFUL OR FATAL IF SWALLOWED! If swallowed, do not induce vomiting. **CALL PHYSICIAN IMMEDIATELY!** Use protective measures to avoid contact with eyes and skin. In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. In case of accidental injection by power spray equipment, **GET MEDICAL ATTENTION IMMEDIATELY! USE ONLY WITH ADEQUATE VENTILATION.**

Avoid breathing of vapor. If you experience eye watering, headaches or dizziness, leave area or increase fresh air or wear respirator (NIOSH/MSHA TC 23C or equal). Repeated and prolonged occupational overexposure to solvent vapor may cause permanent brain and nervous system damage and may cause liver or kidney damage.

KEEP OUT OF REACH OF CHILDREN!

WARNING! This product contains detectable amounts of chemicals known to the State of California to cause cancer, or birth defects or other reproductive harm.

Employers should obtain a copy of the Material Safety Data Sheet (MSDS) from your supplier or directly from Henry at the toll-free number or website below.