

PHYSICAL PROPERTIES

Appearance Black liquid	Consistency @ 77°F Light-bodied liquid	Solids by Volume 38.8%
Base Air blown asphalt	Flash Point -138°F (ASTM D-3278)	Solids by Weight 44.8%
CARB: Primer Max. MIR 1.20	Maximum VOC 550 g/L	Weight per Gallon 7.34 lbs.
Color Black	Maximum VOS 4.59 lbs./gallon	

APPROVALS AND CERTIFICATIONS

Meets or exceeds the requirements of ASTM D-41, and Federal Specification SS-A-701B.

DESCRIPTION

EnduraRoof Quick Dry Asphalt Primer is a light-bodied, asphalt-based material designed for priming surfaces prior to the application of hot-mopped or cold-applied asphalt coatings, roof cements and asphalt-based roof and flooring adhesives. Its highly penetrating qualities help assure a firm, tough bond.

NOTE: **EnduraRoof Quick Dry Asphalt Primer** in the spray can size complies with Air Quality Management District regulations.

USAGE

- Metal edging and flashings
- Weathered composition roofing
- Concrete and masonry surfaces (prior to the use of solvent-based asphalt coatings or adhesives)
- Gypsum surfaces (prior to the use of solvent-based asphalt coatings or adhesives)
- Roofing surfaces prior to application of Ruftac® or other SBS self-adhering membrane

NOTE: For priming concrete, masonry or other porous surfaces to receive asphalt emulsion, use the emulsion diluted 20% with water.

SURFACE PREPARATION

Surface must be clean, dry, free of moisture as well as grease and oil.

APPLICATION

Shake can vigorously until ball rattles freely before using. Apply with good coverage to a clean, dry surface. Allow to dry thoroughly before applying coatings or adhesives. Avoid over-application and build-up of surface film. After spraying, turn can upside down, point nozzle into refuse can or at paper and push spray head for about 2 seconds to clear valve. If valve clogs, remove from can and clean in paint thinner.

EnduraRoof Quick Dry Asphalt Primer

COVERAGE

Coverage is 33 sq. ft. per can depending on porosity of surface.

CLEAN-UP

Equipment can be cleaned with kerosene or mineral spirits. Clean hands with waterless hand cleaner. Use care in handling solvents.

PACKAGING

17 oz. aerosol (1.65 lbs.)

CAUTION

DANGER! EXTREMELY FLAMMABLE! DO NOT PUNCTURE, INCINERATE OR BURN CAN EVEN WHEN EMPTY.

Exposure to heat or prolonged exposure to sun may cause bursting.

CAUTION! COMBUSTIBLE! Contains petroleum distillate and hydrocarbon propellants. Keep away from heat, sparks and flame. Do not heat container or store at temperatures greater than 110°F. CLOSE AIR INTAKES until solvents dissipate. Contains volatile solvents that might contaminate potable water. Close container after each use. Dispose of container and unused contents in accordance with Local, State and Federal regulations.

DANGER! HARMFUL OR FATAL IF SWALLOWED! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY! Use protective measures to avoid contact with eyes and skin. In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. GET MEDICAL ATTENTION! USE ONLY WITH ADEQUATE VENTILATION!

Avoid breathing of vapor. If you experience eye watering, headaches or dizziness, leave area or increase fresh air or wear respirator (NIOSH/MSHA TC 23C or equal). Repeated and prolonged occupational overexposure to solvent vapor may cause permanent brain and nervous system damage and may cause liver or kidney damage.

KEEP OUT OF REACH OF CHILDREN!

WARNING! This product contains detectable amount of chemicals known to the State of California to cause cancer, or birth defects or other reproductive harm.

Employers should obtain a copy of the Material Safety Data Sheet (MSDS) from your supplier or directly from Henry at the toll-free number or website below.