

ROOF X TENDER® 325 NON-FIBERED ASPHALT EMULSION

DESCRIPTION:

ROOF X TENDER® 325 Non-Fibered Asphalt Emulsion is a highly versatile, professional grade coating for application to built-up, mineral surfaced, modified (both SBS and APP) ,metal, concrete, corrugated and other roof surfaces. It can be used alone or in combination with polyester when installing roof restoration systems. It is non-flammable, low odor and bonds to damp or dry surfaces. It can also be used for dampproofing above or below grade foundation walls, sealing masonry surfaces and retaining walls and as an anti-corrosive wood, metal, and pipe coating. DO NOT ALLOW PRODUCT TO FREEZE.

PREPARATION:

All surfaces must be clean, have proper drainage and be free of surface rust, dust and any other foreign matter. Roof surface may be damp (from morning dew), however surfaces may not be saturated with water. Brush clean all cracks, holes, and damaged or rusted areas with a wire brush. Repair using approved ROOF X TENDER® Sealant in a 3 course fashion. DO NOT HEAT OR THIN. DO NOT APPLY IF RAIN IS EXPECTED WITHIN 36 HOURS.

FOR BEST RESULTS:

Always check weather forecast prior to preparation & application.

APPLICATION:

For exterior use only. Protective clothing, gloves, and eyewear should be use during application of this product. Always apply on a clear, warm sunny day. Apply in morning hours to allow maximum cure time. Application should be completed a minimum of 4 hours prior to sunset. Temperatures must be above 55 °F (for 24 hours) and rising, but not above 110 °F. Apply using professional airless sprayer, brush or 1/2" to 3/4" nap roller. Cure times vary depending on coverage rates, humidity, temperature and texture of surface. Allow a minimum of 4 hours between coats. DO NOT APPLY TO DRIVEWAY SURFACES.

COVERAGE RATE:

1 - 8 gal/sq, depending on guide specifications, surface type, texture, condition and porosity.

SPRAY INFO:

1000 - 1500 PSI, .061 - .099 Tip Size, 3 - 6 GPM

CLEAN-UP:

Clean tools with warm water and soap.



- GREAT FOR USE IN COLD PRECESS ROOFING
- USE WITH POLYESTER OR CHOPPED GLASS
- PREPARES SURFACE FOR SILICONE COATINGS



Contains petroleum based products. If swallowed DO NOT induce vomiting. Call physician immediately. In case of: Eye contact - flush with plenty of water; Skin contact - wash thoroughly with soap and water; Irregular or stopped breathing - administer oxygen, give artificial respiration and get medical attention immediately. Avoid prolonged breathing of vapor or spray mist. (NIOSH/MSHA TC 23C or equivalent). Do not use in drinking water or food systems.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING:

This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

CAUTION:

MAY BE HARMFUL OR FATAL IF SWALLOWED. EYE, SKIN AND RESPIRATORY IRRITANT. Use with adequate ventilation. Keep out of the reach of children.

SPECIFICATION DATA: Exceeds performance requirements of ASTM D1227, TYPE III, Class I. UL CLASS A RATED File #R11333.

Weight Per Gallon 8.5 lbs/gal	Skin Time (50% Relative Humidity, 70 °F) 4 - 8 hours
Residue by Evaporation 45%	Full Cure (50% Relative Humidity, 70 °F) 24 - 48 hours
Adhesion to Polyurethane Foam Excellent	Application Temperatures 55 °F - 110 °F
Tool Application Brush or Spray	Clean-up Tools Warm Water & Soap

*percentage may vary +/- 5%

SHIPPING WEIGHTS:

5 gallons (18.9L)	VOC/VOS
45 lbs.	<10 g/L

PETROLEUM ASPHALT	C.A.S.# 8052-42-4
CLAY	C.A.S.# 1332-58-7
WATER	C.A.S.# 7732-18-5