



TRI-BUILT® #40 ORGANIC BASE SHEET

Product Description:

TRI-BUILT #40 Organic Base Sheet is manufactured from superior quality organic felt that is saturated with asphalt and then coated on both sides with weathering grade asphalt and then covered on top with mineral surface fines to prevent sticking in the roll.

Certifications:

Manufactured to comply with:
ASTM D2626

Installation:

#40 OBS base sheet can be used for commercial as well as residential roofing systems. #40 OBS base sheet is applied over the flat roofing deck or insulation before the application of Built-Up Roofing systems. Follow building code and local amendments when installing #40 OBS. Refer to the Tile Roofing Institute (TRI) manual when used as a clay or concrete tile underlayment.

Technical Data

Typical Properties	2.0 square roll
Average Weight of roll	78.0 lbs
Mass of Asphalt Saturant	7.2 lbs / 100 ft sq
Mass of desaturated felt	5.2 lbs / 100 ft sq
Saturation efficiency (min) by weight	70%
Breaking Strength at 77F (min)	
Machine direction	35 lbf/in
Cross Direction	20 lbf/in
No. of Rolls per Pallet	25
Width	39 3/8 Inches
Length	65 feet 10 Inches
Coverage	216 Sq. Ft
Packaging	25 Rolls Per Pallet 25 Pallets Per Truckload



Exposure

#40 OBS can be left exposed for 180 days from date of application. It is the contractors responsibility to repair any areas where damage to underlayment has occurred due to “workbench abuse” prior to application of primary roofing material.

Warranty:

TRI-BUILT offers a 15 year limited material warranty on single ply and 30 year limited material warranty on double ply to approved applicators. Please contact your TRI-BUILT representative for full details.