



TRI-BUILT® ROOF HATCH SAFETY RAILING

TRI-BUILT® OSHA compliant Safety Railing is ideal for new and retrofit applications. The safety railing mounts to the existing roof hatch curb counterflash without penetrating the membrane.

MATERIAL: Rails and posts, aluminum, 1-1/4 inch ID (1.66 inch OD) Schedule 40 pipe.

FITTINGS: Cast aluminum alloy with set screw hold.

MOUNTING BRACKETS: 3/16 inch steel, zinc plated with nut backing plate.

HARDWARE: Hex head bolts 3/8 inch - 16 x 3/4 inch zinc plated steel.

EXIT: Must be kept closed when roof hatch door is open.

- **SELF CLOSING GATE:** Aluminum 1-1/4 inch tubular self closing with coil spring.
- **CHAIN:** 3/16 inch zinc plated steel link chain with spring clip ends.

COMPLIANCE: OSHA 29 CFR1910.23 guarding floor and wall openings and holes.

SIZES: Industry standard and custom sizes available.



SELF CLOSING GATE

Designed to automatically close, the gate is constructed with spring loaded hinges to protect against falls.

CHAIN CLOSURE

Comes with standard chain barrier with easy spring clip attachment to guard against falls.

EASY FIELD INSTALLATION

No field cutting required as rails cut to exact size. Easy assembly fittings and quick mounting on counterflash using a patented nut backing plate.