



TRI-BUILT® HYBRID CONSTRUCTION SEALANT

PRODUCT DESCRIPTION:

TRI-BUILT® Hybrid Construction Sealant is a high performance, chemically curing hybrid sealant that offers excellent adhesion to many substrates including wood, concrete, metal, glass, tile, brick, vinyl, and asphalt shingles.

TRI-BUILT® Hybrid Construction Sealant can be used as an interior/exterior sealant, withstands adverse weather conditions, is UV resistant, is tolerant to damp surfaces, and features minimal shrinkage.

PRODUCT BENEFITS:

- Meets ASTM C 920, Type S, Grade NS, Class 50, use NT, A, M, and G
- Interior/exterior
- UV resistant
- Applies in damp or dry conditions
- Paintable with latex-based paints

BASIC USES:

- Interior & exterior applications:
- Most non-traffic-bearing joints.
- Primerless application to brick, concrete, metal, glass, treated and untreated wood, asphaltic materials, and vinyl
- Through-roof penetrations, flashings, gutters, solar panel installation
- Under decking installation
- Windows and doors
- As a trim sealant for a metal components

ADHERES TO:

Coated steel, Aluminum, Wood, glass, tile, brick, asphalt shingles, EPDM, Fibercement board, skylights, primed TPO, primed PVC, and other common building substrates.

COMPOSITION AND MATERIALS:

Advanced proprietary, hybrid technology.

GRADE: Gun grade, non-sag consistency.

PRIMER: Good primerless adhesion to many common building substrates. However, for joints where high movement is anticipated, the use of a primer is recommended. If primerless adhesion to a particular substrate is in question, a test application is recommended.

PACKAGING: 10.1 fl oz cartridge



COLORS: Black, Brown, Dark Bronze, Medium Bronze, Light Stone, Terra Cotta, White

LIMITATIONS:

- Do not use on traffic-bearing surfaces
- Do not use in areas where food is stored or processed
- Do not use for portable water applications

INSTALLATION

JOINT DESIGN: The width of the joint should be a minimum of 4 times the anticipated movement. In joints up to 1/2" wide, the depth of the sealant should be equal to the width, but not less than 1/4". For larger joints and where the joint depth exceeds 5/16", use a polyethylene backer rod that is 25% larger than the joint opening. Install all joint applications per ASTM recommendations and guidelines. Joints must have a depth to width ratio of 1:2 (joint depth 1/2 of the width). To prevent three-point contact, a backer rod or bond breaker tape must be used to ensure proper joint movement and a weatherproof seal.

SURFACE PREPARATION: Joint surfaces must be dry, clean, and free of all contamination. Glass, metal, and other non-porous surfaces must be free of any coatings and be wiped clean with solvent. Follow manufacturer's instructions for safe use. Precast panels using form-release agents other than polyethylene film must be sand blasted or mechanically abraded and blown or brushed free of dust.

JOINT BACKING: Joint depth should not exceed 3/8". An open cell backer rod should be used to control joint depth. In shallow joints, a bond breaker tape should be installed to prevent three-point contact.

TRI-BUILT® data sheets are updated on a regular basis; it is the user's responsibility to obtain and to confirm the most recent version. Information contained in this data sheet may change without notice.

TRI-BUILT® HYBRID CONSTRUCTION SEALANT

APPLICATION AND TOOLING: Trim nozzle to between 1/4" – 3/8". Smaller openings can cause back pressure, resulting in leaks around the plunger and run-on out of the nozzle. Puncture inner foil liner. Place cartridge in a conventional caulking gun and apply with steady pressure, filling joint completely. Tool into seams and cracks immediately after application.

PAINTING: May be painted immediately after application with latex-based paints.

CLEANING: Remove TRI-BUILT® Hybrid Construction Sealant from gun and tools before it cures. This may be done by scraping and the use of regionally available solvents. Follow manufacturer’s instructions for safe use. Cured materials may be removed by cutting with sharp tools or sandpapering.

STORAGE LIFE: 18 months

CAUTIONS: CONTAINS CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer’s directions for respirator use. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area.

THE ORETICAL YIELD

Per 10.3 fl. oz. cartridge

JOINT SIZE	LINEAR FEET
1/4" x 1/4"	24.1
1/4" x 3/8"	16.0
1/4" x 1/2"	12.4
1/2" x 3/8"	8.4
1/2" x 1/2"	6.0
3/4" x 1/2"	4.0

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Warning: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.**

LIMITED WARRANTY: If when applied according to label directions this product fails to perform in accordance with its published literature, upon satisfactory evidence of product failure, and as your sole remedy, we will either replace the product at no cost or refund the original purchase price for that portion of product that fails to performing accordance with this limited warranty.

Viscosity	550000 to 680,000 cps
Elongation (D412)	230%
Tensile Strength (D412)	220 psi
Shore A Hardness	28
Tack Free Time	90 minutes
Cure	3 days
Application Temperature	0°F to 120°F (-18°C to 49°C)
Service Temperature	-40°F to 200°F (-40°C to 93°C)