

TRI-BUILT LOW RISE FOAM CANISTERS PART ONE

SECTION 1: PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME:	TRI-BUILT LOW RISE FOAM CANISTERS PART ONE	
	ONE COMPONENT OF A TWO-COMPONENT	DISTRIBUTED BY: Beacon Sales Acquisition, Inc.
PRODUCT USE:	POLYURETHANE SYSTEM	ADDRESS: 505 Huntmar Park Drive, Suite 300
MANUFACTURER:	OMG, Inc.	Herndon, VA 20170
ADDRESS:	153 Bowles Road	PHONE: 571-323-3939
	Agawam, MA 01001 USA	INTERNET: www.becn.com
PHONE:	Phone: (01) 413-789-0252	
	Fax: (01) 413-786-1453	
	www.OMGRoofing.com	
EMERGENCY PHONE:	Chemtrec: 800-424-9300	
EFFECTIVE DATE:	12/23/2019	

2. HAZARDS IDENTIFICATION

Classifications: Acute Toxicity, Inhalation: Hazard Category 4
Respiratory Sensitization: Hazard Category 1
Skin Sensitization: Hazard Category 1
Skin Irritation: Hazard Category 2
Eye Irritation: Hazard Category 2B
Specific Target Organ Toxicity, Single Exposure: Hazard Category 3
Specific Target Organ Toxicity, Repeated Exposure: Hazard Category 2
Gases Under Pressure: Compressed Gas
Physical Hazards Not Otherwise Classified: None
Health Hazards Not Otherwise Classified: None

Symbols: Health Hazard
Exclamation Point
Gas Cylinder



Signal Word: Danger

Hazard Statements: May be harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause respiratory irritation.
May cause an allergic skin reaction.
Causes eye and skin irritation.
May cause damage to the respiratory system and/or skin through prolonged or repeated exposure.
Contains gas under pressure; may explode if heated.

Precautionary Statements: Do not breathe mist, spray, or vapors.
Use only outdoors or in a well-ventilated area.
In case of inadequate ventilation wear proper respiratory protection.
Wear protective gloves and eye protection.
Wash hands and forearms thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.

IF INHALED: remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms or if you feel unwell, call a doctor or Poison Control Center.

TRI-BUILT LOW RISE FOAM CANISTERS PART ONE

2. HAZARDS IDENTIFICATION (continued)

Precautionary Statements: (continued) **IF ON SKIN:** Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs, get medical advice/attention.

IF IN EYES: Rinse cautiously with water for at several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Get medical advice/attention if you feel unwell.

Protect from sunlight. Store in a well-ventilated place.

Store locked up in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with applicable regulations.

Other Hazards None known

EMERGENCY OVERVIEW

Overexposure to components of this product by inhalation may cause respiratory irritation, asthma-like symptoms, and/or respiratory sensitization.

Skin contact may cause irritation and/or allergy-like symptoms, and eye contact may cause irritation. Avoid skin and eye contact, using proper personal protective equipment as needed. See Section #7 for recommendations on proper handling and work practices, and Section #8 for recommendations on personal protective equipment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredient</u>	<u>CAS Number</u>	<u>Percentage</u>	<u>Impurities</u>
4,4'-Methylenediphenyl Diisocyanate	101-68-8	25-50	None known
Diphenylmethane Diisocyanate, Isomers and Homologues	9016-87-9	>50	None known
1,1,1,2-Tetrafluoroethane	811-97-2	10-25	None known

4. FIRST AID MEASURES

Eyes: Hold eyes open and flush with lukewarm water for at least 15 minutes. Seek immediate medical assistance.

Skin: Remove contaminated clothing. Wash affected areas with soap and water for at least five minutes. If irritation persists or a rash occurs, seek medical attention. Launder or dry-clean clothing before reuse.

Ingestion: DO NOT induce vomiting. If the subject is conscious, wash mouth with water. Seek immediate medical assistance. Do not attempt to give anything by mouth to an unconscious or convulsive person.

TRI-BUILT LOW RISE FOAM CANISTERS PART ONE

Inhalation: If signs and symptoms of respiratory toxicity are observed, remove subject from area and seek immediate medical attention. Keep the subject warm and at rest. If necessary, administer oxygen or perform artificial respiration if necessary and qualified personnel are available to do so.

4. FIRST AID MEASURES (continued)

Guidance for Physician or Poison Control Center: Inhalation exposure can irritate the respiratory tract and induce respiratory sensitization. Treatment of acute irritation and bronchial constriction should be done according to symptoms. Eye contact can cause irritation. Skin contact can cause moderate irritation and may elicit an allergic response among susceptible individuals. Treat eye and skin irritation or injury according to symptoms. Extended medical treatment may be necessary for individuals exhibiting respiratory sensitization and/or skin disorders.

5. FIREFIGHTING MEASURES

Extinguishing Media: Water spray, carbon dioxide, dry chemical or chemical foam. DO NOT use water jet.

Fire and Explosion Hazards: The container may burst if exposed to elevated temperatures, spilling the contents. Material reacts slowly with water, releasing carbon dioxide which can cause pressure buildup and rupture of closed containers. If present in a fire or explosion, potential decomposition byproducts include carbon monoxide, oxides of nitrogen, isocyanates, and hydrogen cyanide.

Firefighting Instructions: If fighting a fire in which this product is present, wear a self-contained breathing apparatus with full-facepiece operated in pressure-demand or other positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Methods and Materials: Absorb spilled material with a sorbent such as sawdust or calcium silicate hydrate. When absorbed, transfer to an impervious container. Neutralize with solution of 8-10% sodium carbonate and 2% liquid detergent in water (10:1 ratio of solution to product). Do not seal container, as CO₂ will be released. Neutralize in a well-ventilated area for at least 48 hours before sealing containers for disposal.

Personal Precautions: Avoid contact with skin, eyes, and mucous membranes. Wear appropriate personal protective equipment (see Section #8) during cleanup and decontamination. Restrict unauthorized personnel during cleanup and disposal operations.

Environmental Precautions: Prevent spills from entering sewers or contaminating soil.

TRI-BUILT LOW RISE FOAM CANISTERS PART ONE

Handling Precautions: Containers should be kept tightly closed to prevent contact with moisture and other chemicals. Do not reuse empty containers for any purpose. When handling the product, avoid contact with eyes, skin, and clothing, using protective equipment as needed. Do not use this product around children and secure it away from children.

7. HANDLING AND STORAGE (continued)

Work and Hygiene Practices: To prevent ingestion or contact following use of the product, wash hands and face before eating, drinking, applying cosmetics, or using tobacco. Remove contaminated clothing and protective equipment before entering eating/drinking areas.

Storage Precautions: Keep containers tightly sealed during storage. Store in a dry, well-ventilated area away from sources of ignition and incompatible materials (see Section #10). Protect from heat and direct sunlight. Recommended temperature for storage is 55-85°F. (12.8-29.4°C.).

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingredients	<u>Ingredient</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Exposure Limits:	4,4'-Methylenediphenyl Diisocyanate	0.02 ppm "C"	0.005 ppm TWA
	Diphenylmethane Diisocyanate, Isomers and Homologues	None	None
	1,1,1,2-Tetrafluoroethane	None	None

Ingredients	<u>Ingredient</u>	<u>Biological Limit(s)</u>
Biological Limits:	4,4'-Methylenediphenyl Diisocyanate	No ACGIH BEIs or other biological limits
	Diphenylmethane Diisocyanate, Isomers and homologues	No ACGIH BEIs or other biological limits
	1,1,1,2-Tetrafluoroethane	No ACGIH BEIs or other biological limits

Engineering Controls: Use appropriate ventilation (dilution or local exhaust) whenever natural ventilation is restricted or inadequate to maintain concentrations of all components within their applicable standards.

Eye/Face Protection: Wear eye protection adequate to prevent eye contact with the product. Plastic-frame spectacles with side shields, chemical goggles, or a face shield are recommended.

Skin Protection: Wear protective gloves and clothing to prevent skin irritation or injury from contact with the product. Glove materials known to be effective against permeation by isocyanates include butyl rubber, nitrile rubber, and polychloroprene.

TRI-BUILT LOW RISE FOAM CANISTERS PART ONE

Respiratory Protection: If an exposure level to a component exceeds an applicable standard, use a NIOSH-approved respirator of a class and configuration effective for protection from the component(s) generated. Where exposures exceed the OSHA *Permissible Exposure Limit (PEL)*, an airline respirator or self-contained breathing apparatus (SCBA) is recommended. Consult OSHA regulations (29CFR1910.134) and/or American National Standard Z88.2 (ANSI, New York, NY 10036, USA) for guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: cream-colored liquid	Lower Explosive Limit: not determined
Odor: aromatic	Upper Explosive Limit: not determined
Odor threshold: not determined	Vapor pressure: 5,716 hPa
pH: not applicable	Vapor density: not determined
Melting point: not determined.	Evaporation Rate: not determined
Freezing point: not determined	VOCs (per EPA Method 24): none
Boiling point: not determined	Relative density (H ₂ O): approx. 1.23
Boiling range: not applicable (aerosol)	Solubility (H ₂ O): reactive
Flash Point: not applicable (aerosol)	Oil-water partition coefficient: not determined
Autoignition Point: not determined	Decomposition temperature: not determined
Flammability Class: not applicable (aerosol)	Viscosity: not determined

10. STABILITY AND REACTIVITY

Stability:	Stable
Reactivity:	May react with water and incompatible materials
Hazardous Polymerization:	May occur at temperatures >392°F./200°C.
Risk of Dangerous Reactions:	None reasonably foreseeable
Incompatible Materials:	Water, alcohols, acids, alkalis, and amines
Potential Decomposition Byproducts:	Carbon monoxide, carbon dioxide, nitrogen oxides, isocyanates, and hydrogen cyanide

11. TOXICOLOGICAL INFORMATION

<u>Ingredients Toxicology Data</u>	<u>LD₅₀ Oral</u>	<u>LD₅₀ Dermal</u>	<u>LC₅₀</u>
4,4'-Methylenediphenyl Diisocyanate	>10,000 mg/kg (rat)	No data available	2.24 mg/l. for 1 hour (rat)
Diphenylmethane Diisocyanate, Isomers and Homologues	No data available	No data available	No data available
1,1,1,2-Tetrafluoroethane	No data available	No data available	>2,300 mg/l. (rat)
Primary Route(s) of Entry:	Inhalation; ingestion		
Eye Hazards:	This product may cause eye irritation.		
Skin Hazards:	This product may cause mild to moderate skin irritation and has the potential to cause skin sensitization among susceptible individuals.		

TRI-BUILT LOW RISE FOAM CANISTERS PART ONE

Ingestion Hazards:	The product is nontoxic by ingestion, but ingestion may cause nausea, vomiting, and/or gastrointestinal irritation.
Inhalation Hazards:	Inhalation of toxicologically-significant quantities of ingredients is unlikely when the product is used in a well-ventilated area and in accordance with instructions.
Symptoms Related to Overexposure:	Inhalation overexposure to isocyanates may cause respiratory irritation, breathing difficulties, and asthma-like symptoms.

11. TOXICOLOGICAL INFORMATION (continued)

Delayed Effects from Long Term Overexposure:	Long-term inhalation overexposure to this product may result in respiratory damage, which may be irreversible.
Carcinogenicity:	A single inhalation study exposing rats to aerosolized polymeric 4,4'-Methylenediphenyl Diisocyanate identified a single malignant pulmonary tumor among sixty animals exposed at the highest exposure level. Observations of pulmonary fibrosis and other pathological anomalies in the test animals precluded definitive determination as to the cause(s) of the tumor. Epidemiological studies of humans occupationally exposed to the isocyanates in this product have found no strong association or consistent pattern with respect to carcinogenicity.
Germ Cell Mutagenicity:	No ingredients have been determined to be germ cell mutagens.
Reproductive Toxicity:	No ingredients have been determined to be damaging to fertility or to the unborn child.
Acute Toxicity Estimates:	LD ₅₀ (oral): >10,000 mg/kg LD ₅₀ (dermal): >9,400 mg/kg LC ₅₀ : 2.24 mg/L/1 hr as aerosol
Interactive Effects of Components:	No data available

12. ECOLOGICAL INFORMATION

4,4'-Methylene-diphenyl Diisocyanate	Aquatic Toxicity to Fish: LC ₅₀ >1,000 mg/l. for 96 h. (zebra fish) Aquatic Toxicity to Invertebrates: EC ₅₀ >1,000 mg/l. for 24 h. (daphnia) Aquatic Toxicity to Plants: EC ₅₀ >1,640 mg/l. for 72 h. (algae) Aquatic Toxicity to Microorganisms: EC ₅₀ >100 mg/l. for 3 h. (bacteria) Toxicity to Terrestrial Organisms: EC _{No} = 1,000 mg/kg for 14 d. (worms) No data available for Persistence and Degradability, Bioaccumulation Potential, or Mobility in Soil.
Diphenylmethane Diisocyanate, Isomers and homologues	No data available for Aquatic Toxicity to Fish, Invertebrates, Plants, or Microorganisms, Toxicity to Terrestrial Organisms, Persistence and Degradability, Bioaccumulation Potential, or Mobility in Soil.

TRI-BUILT LOW RISE FOAM CANISTERS PART ONE

1,1,1,2-Tetrafluoroethane	Aquatic Toxicity to Fish: LC₅₀ = 450 mg/l. for 96 h. (rainbow trout) Aquatic Toxicity to Invertebrates: EC₅₀ = 950 mg/l. for 48 h. (daphnia) Aquatic Toxicity to Plants: EC₅₀ = 118 mg/l. for 72 h. (algae) No data available for Aquatic Toxicity to Microorganisms, Toxicity to Terrestrial Organisms, Persistence and Degradability, Bioaccumulation Potential, or Mobility in Soil.
Ozone Depletion Potential:	This product neither contains nor is manufactured with any ingredients known to deplete the ozone layer.

13. DISPOSAL CONSIDERATIONS

Do not discharge waste product into sanitary or storm sewers or allow it to contaminate soil. Empty containers should be decontaminated prior to disposal. Consult applicable Federal, State/Provincial, and local regulations.

14. TRANSPORTATION INFORMATION

Proper Shipping Name: Chemical Under Pressure, n.o.s.
 (contains fluorinated hydrocarbon, nitrogen)
 Identification Number: UN3500
 Hazard Class: 2.2
 Packing Group: not applicable

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA Information:	All ingredients of this product are listed in the TSCA Registry.
SARA Hazard Classes:	Refer to Section 2 for the OSHA Hazard Classification
EPCRA Section 313 Notification:	This product contains these ingredients in concentrations ≥1% (for carcinogens ≥0.1%) regulated under Section 313 of the <i>Emergency Planning and Community Right-To-Know Act</i> of 1986 or 40 CFR 372: 4,4'-Methylenediphenyl Diisocyanate (CASRN 101-68-8) - Diphenylmethane Diisocyanate, Isomers and Homologues (CASRN 9016-87-9)
CERCLA Information:	Under requirements of the <i>Comprehensive Environmental Response, Compensation, and Liability Act</i> (CERCLA), 4,4'-Methylene Bisphenyl Isocyanate (CASRN 101-68-8) has a <i>Reportable Quantity</i> of 5,000 lbs. Any spill or release above this <i>RQ</i> must be reported to the National Response Center (800-424-8802).

Canadian Regulatory Information

All ingredients in this product are listed in the Domestic Substances List (DSL) or the Nondomestic Substances List (NDSL).

TRI-BUILT LOW RISE FOAM CANISTERS PART ONE

16. OTHER INFORMATION

Hazardous Materials Information System (HMIS III) Ratings (Legend):	<u>Health</u> 2* (moderate hazard, “*” indicating potential for chronic effects)	<u>Flammability</u> 0 (minimal hazard)	<u>Physical Hazard</u> 1 (slight hazard)	<u>PPE</u> See Note
---	--	--	--	------------------------

16. OTHER INFORMATION (continued)

Note regarding PPE: OMG, Inc. recommends use of protective eyewear and skin protection (Personal Protection Index "B") as standard PPE for the anticipated conditions of use of this product. However, HMIS recommends that its ratings be used only in conjunction with a fully implemented HMIS program, and that specific PPE codes should be created by the user, who is familiar with the actual conditions under which the product is used. We cannot anticipate every condition of the product's use, and it is the user's responsibility to evaluate the hazards pertinent to its specific operations, and to determine the specific PPE required.

National Fire Protection Association (NFPA) Ratings:	<u>Health</u> 2	<u>Flammability</u> 0	<u>Reactivity</u> 1
--	--------------------	--------------------------	------------------------

Revision Information: Publication Date: 11 September 2020
Date of Prior SDS: 24 January 2018

DISCLAIMER

Our products and the information contained herein are supplied on the condition that the persons receiving same will make their own determination as to suitability for their purposes prior to use. In no event will OMG be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this sheet or the products to which the information refers. OMG does not warrant the accuracy or timeliness of the information in this sheet and has no liability for any errors or omissions in these materials. **The information contained in this SDS was provided by a third party to OMG.**

THIS SHEET IS PROVIDED ON AN "AS IS" BASIS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION PROVIDED OR THE PRODUCTS TO WHICH THE INFORMATION REFERS.