



Our NEWEST Advanced Feature Low Profile Vent!



Fully supported nail holes.



External Venturi and "Omni" baffles provide enhanced airflow.



Unique "posi-tabs" contour to shingles for improved weather protection.



Continuous molded end plug and underlap prohibit weather infiltration.

PRO4-N FEATURES

- Advanced low profile design.
- Includes 2½" ring shank nails, 30 nails per piece
- Internal baffles
- External "Omni" baffles
- External Venturi baffle
- "Posi-tabs" contour to shingles for improved weather protection
- Weatherproof underlapping joints
- 6 drain holes per side per foot
- 18 square inches of Net Free Area per linear foot
- 10 supported nail holes
- Preformed to 2/12 pitch
- Fits roof pitches 2/12 to 16/12
- Molded-in shingle nail lines, reinforced every 2 inches
- Slot width guide lines
- Continuous molded end plug for improved weather protection
- **Lifetime Limited Warranty**

Model	Length (ft.)	NFA (in. ²)	Roof Pitch	Packaged
PRO4-N	4'	72	2/12 To 16/12	10 Per Box

PRO4-N Ventilation Guide

(Attic floor space) in square feet

Area Ventilated	1000	1500	2000	2500	3000	3500
PRO4-N Required (ft.)	14'	20'	27'	34'	40'	47'
Intake Required (in ²)	252	360	486	612	720	846

Based on the IRC/FHA standard of one square foot of ventilation for every 300 square feet of attic floor space.

MADE IN THE USA

MIAMI-DADE COUNTY
APPROVED

19-1217.04

FBC
FL28475-R1