



TRI-BUILT® ROOF ACCESSORY PAINT

TRI-BUILT® Roof Accessory Paint is a fast-drying enamel with built-in metal corrosion protector used to hide flaws, blemishes, and unsightly roof protrusions. It provides superior protection, durability, and adhesion.

- Adds final touch with a professional finish
Hides flaws, blemishes, and unsightly roof protrusions
- Provides a smooth, durable, rust fighting finish that prevents stains
- Dries in 8 minutes or less
- Basic Uses: Asphalt shingles, aluminum, metal, PVC, other plastics & more



					
White TB0371101	Weathered Wood TB0371102	Brown TB0371104	Cedar TB0371108	Gray TB0371124	Slate TB0371131
					
Charcoal TB0371132	Deep Brown TB0371134	Terra Cotta TB0371135	Birchwood TB0371136	Hickory TB0371151	Dark Gray TB0371133

TRI-BUILT® ROOF ACCESSORY PAINT

SURFACE PREPARATION: WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log onto www.epa.gov/lead. Surface should be clean, dull & dry. Remove loose rust & paint with the wire brush or sandpaper.

PAINTING CONDITIONS: Spray outdoors or in a well-ventilated area. Protect surrounding areas. Best results are achieved when air and surface temperature are between 40-80°F. For best results, do not use in high humidity. DO NOT PAINT OBJECTS WHILE THEY ARE HOT.

APPLICATIONS: Shake can for 2 minutes after ball within begins to rattle. Continue to shake for 10 seconds after each minute of use. Test spray in an inconspicuous area for compatibility. Hold can 8-12" from surface, spray in sweeping motion side to side with slight overlap. Apply multiple thin coats.

COVERAGE: Approximately 25 sq. ft.

DRY TIME: Dry to touch in 8 minutes. Tack free in 15 minutes. Apply additional coats within 2 hours or after 8 hours.

AFTER USE: To prevent clogs, hold can upside down and spray until clear gas appears. To clean paint on actuator, wear eye protection and wipe off with lacquer thinner- DO NOT stick pin in opening. Recycle empty can per local regulations.

STORAGE LIFE: Three years

CONTAINS KETONES AND TOLUENE. DANGER! EXTREMELY FLAMMABLE. Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. DO NOT SMOKE - Extinguish all flames, pilot lights and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. CONTENTS UNDER PRESSURE. Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water, and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Keep upright in a cool, dry place. Do and does not include labor or costs associated with the application or removal of any product. IN NO EVENT SHALL TRI-BUILT® BE LIABLE FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE, OR INDIRECT DAMAGES WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY. Some states

do not allow limitations on how long an implied warranty lasts or limitations on incidental or consequential damages, so portions of the limitations above might not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary from state to state. Danger: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations not discard empty can in trash compactor. VAPOR HARMFUL. Use with adequate ventilation. Avoid continuous breathing of vapor and spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. SEE SAFETY DATA SHEET. DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

PERFORMANCE TESTING: Technical data furnished herein is accurate and true to the best of our knowledge. However, no guarantee of accuracy is express or implied. We assume no responsibility or liability as a result of purchase, coverage, application, or injuries resulting in misuse.

LIMITED WARRANTY: This warranty is made to you, the product purchaser who owns the property where the product is applied. This warranty is not transferable except that if a contractor purchased and applied the product to the property for you, then the warranty is transferable to you. If this product, when applied and maintained according to product application and maintenance instructions to a properly prepared surface,

fails to perform, contact us at 571-323-3939 and upon satisfactory evidence of product failure, and with your proof of purchase, you may either receive a replacement of an equivalent quantity of product free of charge, or request a refund from the store where purchased. This warranty shall not apply to any defect, damage, or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application or maintenance of the product. Your sole remedy, and the sole liability of TRI-BUILT® under this warranty is the replacement of product or refund and does not include labor or costs associated with the application or removal of any product. IN NO EVENT SHALL TRI-BUILT® BE LIABLE FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE, OR INDIRECT DAMAGES WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY. Some states do not allow limitations on how long an implied warranty lasts or limitations on incidental or consequential damages, so portions of the limitations above might not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary from state to state.

DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.